



**SITE LIGHT FIXTURE INFORMATION**

**DIMENSIONS**

**TLM TALON MEDIUM LED**

**Optics**  
 Choice of twelve patented, high-efficiency AccuLED Optics™ distributions. Optics are precisely designed to shape the light output, maximizing efficiency and application spacing. AccuLED Optics technology creates consistent distributions with the scalability to meet customized application requirements. Offered Standard in 4000K (+/- 275K) CCT and minimum 70 CRI. Optional 3000K CCT, 5000K CCT and 5700K CCT. For the ultimate level of spill light control, an optional house-side shield accessory can be field or factory installed. The house-side shield is designed to seamlessly integrate with the SL2, SL3 or SL4 optics.

**MOUNTING CONFIGURATIONS**

Wall Mount	Arm Mount Single EPA 1.89	Arm Mount 2 @ 180° EPA 3.55	Arm Mount 2 @ 90° EPA 5.43	Arm Mount 3 @ 120° (Round Pole Only) EPA 3.19	Arm Mount 3 @ 90° EPA 3.52	Arm Mount 4 @ 90° EPA 4.17
------------	------------------------------	--------------------------------	-------------------------------	---	-------------------------------	-------------------------------

**SITE LEGEND**

- CROSSWALK
- SITE PROPERTY LINE
- SITE P.U.E.
- SITE BUILDING SETBACK
- SNOW STORAGE AREA
- LANDSCAPE -- SEE LS101
- LIGHTING -- SEE ES101